

DICHOIC MR16 Ø51 - With transparent safety glass



- * Wide choice of wattages and beam apertures.
- * Version with safety glass.
- * Dichroic coating of the reflector: sends the heat towards the back of the lamp.

Item Characteristics

Code	01266
Lamp Voltage	12 V
Nominal Power	35 W
Base	GU5,3
Lamp Current	2,91 A
Nominal Flux	455 LUMEN
Type of lamp	With safety glass
Colour temperature	3000 K
Opening beam	38°
Diameter	51 mm
Lenght	45 mm

Performance

ANSI	FMW
Axis cd	1000
Irc/Ra	100
Lifetime	2000 h
Energy Class	B
kWh/1000h	38
Equivalence with incandescent lamp	45 W

Tech Info

Dimmable	NO
Operating Position	360°
Number of ON-OFF cycles	25000
Power Factor	1
Warm-up time up to 60 % of the full light output	Instant Full Light
Lamp start time	<0,2s
T (°C) Working environment Temp.	-15°C / +35°C
Fulfilled Directives and norms	2011/65/UE * RoHS EN60432-3 * Anno 2013 2010/30/EU * Energy Consumption 874/2012 * Regulation for Energy Labelling 2009/125/CE * Progettazione Eco Compatibile 1194/2012 * Progettazione Eco Compatibile

Shipping info

Single pack dimensions L x H x D (mm)	50 x 50 x 50
Item barcode	8011905011789
Pack	20 pz

Inner pack dimensions L x H x D (mm)	257 x 54 x 212
Master barcode	8011905700904
Master pack dimensions L x H x D (mm)	450 x 300 x 280