

## DURADISK LED - Colors



- \* Base: GX53.
- \* Working from mains no transformer required.
- \* Number of LEDs: 29.
- \* Compact and flexible to use: only 2.6 cm thick.
- \* Fuse for mains protection.
- \* Working position: Universal.
- \* Working Temperature: -25 +40°C.
- \* Extra Long Life.
- \* Diffused light for fantastic colour effects.
- \* No heat on the lamp surface.

### Item Characteristics

Code	07061
Lamp Voltage	220-240 V
Nominal Power	1,0 W
Base	GX53
Opening beam	2x45°
Diameter	75 mm
Lenght	26 mm
Colour	Red
LED Number	29

### Performance

Axis cd	2
Lifetime	>20000 h
kWh/1000h	1

### Tech Info

Dimmable	NO
Lamp start time	<0,2s
LLMMF - Lamp lumen maintenance factor	70
T (°C) Working environment Temp.	25°C
Fulfilled Directives and norms	2006/95/CE * Bassa Tensione 2004/108/CE * Compatibilità Elettromagnetica 2011/65/UE * RoHS 2012/19/UE * RAEE EN 61547 * anno 2010 EN 55015 * anno 2014 EN 61000-3-2 * anno 2007 (+A1/+A2:2011) EN 61000-3-3 * anno 2014 EN 62471 * anno 2010 IEC/TR 62471-2 EN 62031 * anno 2009 (+A1:2013) EN 62560 * anno 2013 EN 60968 * anno 2013 2010/30/EU * Energy Consumption 874/2012 * Regulation for Energy Labelling 2009/125/CE * Progettazione Eco Compatibile 1194/2012 * Progettazione Eco Compatibile

**Shipping info**

---

Item barcode	8011905820572
Pack	10 pz
Master barcode	8011905765859