

DR111 LED AIR



- * Base :G53
- * Operating voltage 12V DC/AC 50Hz.
- * Using High Power EDISON LEDs.
- * Fuse for mains protection.
- * Working position: universal.
- * Do not use with dimmer.
- * Warm white colour temperature.
- * Extra Long Life.
- * Unique design of the heat sink: improves the efficiency of heat dissipation.
- * Compatible with 12V DC/AC 50Hz output electronic transformers for LEDs.
- * Can be used with Duralamp drivers codes DELT20A-12 and DELT50A-12. .
- * Do not use this item with electronic transformers for halogen lamps nor with electromagnetic transformers.

Item Characteristics

Code	07073
Lamp Voltage	12 V
Nominal Power	12 W
Base	G53
Nominal Flux	730 LUMEN
Light Tonality	Cool White
Colour temperature	6000 K
Opening beam	2x12°
Diameter	111 mm
Lenght	57 mm
LED Number	6

Performance

Axis cd	3650
Irc/Ra	>80
Lifetime	>15000 h
Energy Class	A
kWh/1000h	14
Equivalence with incandescent lamp	75 W

Tech Info

Dimmable	NO
Power Factor	0,60
Lamp start time	<0,2s
LLMMF - Lamp lumen maintenance factor	70
T (°C) Working environment Temp.	25°C
Fulfilled Directives and norms	2004/108/CE * Compatibilità Elettromagnetica 2011/65/UE * RoHS 2012/19/UE * RAEE EN 61547 * anno 2010 EN 55015 * anno 2014 EN 61000-3-2 * anno 2007 (+A1/+A2:2011) EN 61000-3-3 * anno 201 EN 62471 * anno 2010 IEC/TR 62471-2 EN 62031 * anno 2009 (+A1/2013) 2010/30/EU * Energy Consumption 874/2012 * Regulation for Energy Labelling 2009/125/CE * Progettazione Eco Compatibile 1194/2012 * Progettazione Eco Compatibile

Shipping info

Item barcode	8011905829506
Pack	10 pz
Master barcode	8011905774783