BIPIN JC FOR BOAT

* Bipins with special voltages.

* Used on boats or installations connected to batteries or generators.

* Can be used with light dimmers.

Item Characteristics

Code	01926
Lamp Voltage	28 V
Nominal Power	10 W
Base	G4
Lamp Current	0,35 A
Nominal Flux	110 LUMEN
Type of lamp	Clear
Colour temperature	3000 K
Diameter	9 mm
Lenght	33 mm

Performance

Irc/Ra	100
Lifetime	2000 h
Energy Class	C
kWh/1000h	11
Equivalence with incandescent lamp	13 W

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products.

Tech Info

Dimmable	YES
Operating Position	360°
UV Stop quarz bulb	YES
Open fittings	YES
Filament	Horiz.
Number of ON-OFF cycles	25000
Power Factor	1
Warm-up time up to 60 % of the full light output	Instant Full Light
Lamp start time	<0,2s
T (°C) Working environment Temp.	-15°C / +35°C
Fulfilled Directives and norms	2009/125/CE * Progettazione Eco Compatibile 2011/65/UE * RoHS 244/2009 * Progettazione Eco Compatibile 859/2009 * Progettazione Eco Compatibile EN60432-3 2010/30/EU * Energy Consumption 874/2012 * Regulation for Energy Labelling

Shipping info

Single pack dimensions L x H x D (mm)	19 x 50 x 19
Item barcode	8011905021696
Pack	20 pz
Inner pack dimensions L x H x D (mm)	105 x 53 x 85
Master barcode	8011905721084
Master pack dimensions L x H x D (mm)	450 x 290 x 225

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products.