

## DECORATIVE COLOURED DICHROIC MR16 Ø51



- \* Externally painted aluminized reflector.
- \* Safety glass integrated with the housing.
- \* The epoxy paint prevents light or heat passing to the back of the lamp.
- \* The coloured reflector acts as a complement for ambients which are particularly attentive to design.

### Item Characteristics

Code	1D01269ST
Lamp Voltage	12 V
Nominal Power	50 W
Base	GU5,3
Lamp Current	4,16 A
Nominal Flux	573 LUMEN
Type of lamp	With safety glass
Colour temperature	3000 K
Opening beam	38°
Diameter	51 mm
Lenght	45 mm
Weight	30 g
Colour	Satine silver reflector

### Performance

ANSI	EXN
Axis cd	1500
Alpha	0,80
Irc/Ra	100
Lifetime	2000 h
Energy Class	C
kWh/1000h	53

### Tech Info

Dimmable	YES
Operating Position	360°
UV Stop quartz bulb	YES
Open fittings	YES
Number of ON-OFF cycles	25000
Power Factor	1
Warm-up time up to 60 % of the full light output	Instant Full Light
Lamp start time	<0,2s
T (°C) Working environment Temp.	-15°C / +35°C
Fulfilled Directives and norms	2011/65/UE * RoHS EN60432-3 * Anno 2013 2010/30/EU * Energy Consumption 874/2012 * Regulation for Energy Labelling 2009/125/CE * Progettazione Eco Compatibile 1194/2012 * Progettazione Eco Compatibile

**Shipping info**

Single pack dimensions L x H x D (mm)	50 x 50 x 50
Item barcode	8011905321581
Pack	20 pz
Inner pack dimensions L x H x D (mm)	257 x 54 x 212
Master barcode	8011905747602
Master pack dimensions L x H x D (mm)	450 x 300 x 280