

DICHROIC GOLD MR16 Ø51 5000h



- * Lifetime: 5,000 hours, 4 times more a regular dichroic lamp!
- * Dichroic coating of the reflector: sends the heat towards the back of the lamp.
- * Optimization of maintenance scheduling.
- * For professional and commercial applications.

Item Characteristics

Code	1D01280L
Lamp Voltage	12 V
Nominal Power	50 W
Base	GU5,3
Lamp Current	4,16 A
Nominal Flux	473 LUMEN
Type of lamp	With safety glass
Colour temperature	3000 K
Opening beam	60°
Diameter	51 mm
Lenght	45 mm
Weight	30 g

Performance

ANSI	FNV
Axis cd	700
Irc/Ra	100
Lifetime	5000 h
Energy Class	D
kWh/1000h	53

Tech Info

Dimmable	YES
Operating Position	360°
Number of ON-OFF cycles	25000
Power Factor	1
Warm-up time up to 60 % of the full light output	Instant Full Light
Lamp start time	<0,2s
T (°C) Working environment Temp.	-15°C / +35°C
Fulfilled Directives and norms	2011/65/UE * RoHS EN60432-3 * Anno 2013 2010/30/EU * Energy Consumption 874/2012 * Regulation for Energy Labelling 2009/125/CE * Progettazione Eco Compatibile 1194/2012 * Progettazione Eco Compatibile

Shipping info

Single pack dimensions L x H x D (mm)	50 x 50 x 50
Item barcode	8011905052874
Pack	20 pz
Inner pack dimensions L x H x D (mm)	257 x 54 x 212
Master barcode	8011905743659
Master pack dimensions L x H x D (mm)	450 x 300 x 280